



- ★ Performed with steel core.
- ★ Excellent resistance to abrasion.
- ★ Longer service life.
- ★ Inside to strands wires grade 1770 N/mm².
- ★ Applications; Bottom Trawling, Pelagic Trawling.

EUROSTEEL® 4 STRANDS (Combination Rope)

Diameter (mm)	Minimum Breaking Load (kgf)	Weight (kg/m)
22	7.400	0,465
28	12.000	0,770
30	12.560	0,810
32	15.280	0,940
34	19.100	1,195
36	21.800	1,350
38	24.040	1,500
40	21.700	1,350
40	26.500	1,680
42	27.700	1,750
44	31.600	2,000
50	40.500	2,500
54	34.500	2,000
60	58.500	3,500

Final Weight Tolerance: 3% - 6%

Final Diameter Tolerance: 2% - 5%



- ★ Performed with fibre core.
- ★ Excellent resistance to abrasion.
- ★ Longer service life.
- ★ Inside to strands and core wires grade 1770 N/mm².
- ★ Applications; Bottom Trawling, Pelagic Trawling.

EUROSTEEL® 6 STRANDS (Combination Rope)

Diameter (mm)	Minimum Breaking Load (kgf)	Weight (kg/m)
12	3.600	0,210
14	4.880	0,290
16	6.150	0,380
18	8.170	0,470
20	9.780	0,580
22	12.790	0,710
24	15.630	0,860
26	18.080	1,010
28	19.640	1,120
30	21.650	1,240
32	25.270	1,430

Final Weight Tolerance: 0% - 6%

Final Diameter Tolerance: 0% - 5%