



## DRAKO 250 T

- ★ 8x19 Warrington construction.
- ★ Preformed, pre - stretched, bright, right hand ordinary lay.
- ★ TÜV Süd certificate CA067 (6.0 mm – 8.0 mm).
- ★ Very low D/d ratio of up to 8 mm in diameter.
- ★ Required drive torque is greatly reduced.
- ★ Cost saving drives possible.
- ★ Flexible with good bending endurance.
- ★ Low elastic and plastic elongation.
- ★ High breaking strength in relation to diameter.
- ★ Marking line for an easy installation.

### Applications:

Traction ropes for mid - rise elevators.



### GENERAL VIEW

Rope Diameter (mm)	Minimum Breaking Load, kN (1570 N/mm <sup>2</sup> )	Minimum Breaking Load, kN (1770 N/mm <sup>2</sup> )	Metallic Area (Approx) (mm <sup>2</sup> )	Weight (kg/100m)
6	-	26,8	18,5	16,4
6.5	-	31,5	20,6	17,9
8	43,3	46,6	31,6	27,3
9	54,8	-	40,0	34,3
10	67,7	72,7	49,4	42,3
11	81,9	-	59,7	51,2
12	97,4	-	71,1	61,0
13	114	-	83,4	71,5
14	133	-	96,7	82,9
16	173	-	126,0	108,3

