




6x19 S - IWRC



8x19 S - FC



6x19 S - FC



6x19 W - FC

## DRAKO (6x19 S, 6x19 W, 8x19 S)

- ★ Preformed, pre - stretched (medium).
- ★ Bright or galvanized right hand ordinary lay.
- ★ Greater reliability and system availability
- ★ Lower susceptibility to breakdown.
- ★ Higher breaking strengths.
- ★ Length and form stability in all environments.

### Applications:

Governor ropes for elevator system.



### GENERAL VIEW

Rope Diameter (mm)	MBL, kN (1370/1770 N/mm <sup>2</sup> )	MBL, kN (1570 N/mm <sup>2</sup> )	MBL, kN (1770 N/mm <sup>2</sup> )	MBL, kN (1960 kN/mm <sup>2</sup> )	Weight (kg/100m)
DRAKO 6x19 S - IWRC					
8	-	35,9	-	-	26,2
DRAKO 8x19 S - FC					
6.5	-	19	-	-	14,6
8	-	-	34,2	-	21,5
9.5	-	-	48,3	-	30,4
10	47,4	47,4	-	-	33,7
12.7	76,5	-	-	-	54,3
DRAKO 6x19 S - FC					
6	-	19	21,4	23,3	13
DRAKO 6x19 W - FC					
5	-	-	14,6	-	9,5
6	-	19,8	-	24,7	13,2
6.3	-	-	-	27,2	14,6
6.5	23,2	23,2	26,2	-	15,5
7	-	-	28,6	-	18
8	-	-	39,6	-	23,6

