HEAVY LIFT ROUND SLINGS (POLYESTER)

G-TEX+

Technical specifications:

- G-TEX PLUS heavy lift slings are used in many different configurations depending the lifting project. (Engineered or repetitive lifting job, static or dynamic loads, etc.)
- High lifting capacity. (Up to WLL 200 tons)
- Double protection sleeve. (Upon request)
- Various protections for sharp edges, corners etc.
- Diverse sling configurations. (Upon request)
- Private label with unique traceability code.
- Extra protections upon request.
- Manufactured according to EN 1492-2 standard.
- Usable at temperature between -40 °C to 100 °C.

WLL (ton)	12	15	20	25	30	40	50	60	70
Inside Dia. (mm)	43	47	55	60	65	75	85	95	100
WLL (ton)	80	85	90	100	125	150	175	180	200
Inside Dia. (mm)	110	115	120	140	160	180	210	230	240

- Fluorescent inner sleeve (shrinking sock).
- Extra core protection, possibility to repair outer sleeve.
- Extra compact, smaller diameter.

- Heavy duty label protection.

- Additional textile protection sleeves with woven in safe working load. Easy to identify.

As of 04/2019 - Güven Çelik Halat reserves the right to make changes to the products shown in this catalogue without prior notice. It does not accept responsibility for visual printing and technical typographical errors.