

## İZMİT 6x19 M (STD)

- ★ Galvanized and bright design.
- ★ More flexible than 6x7 M ropes.
- ★ Resistant to abrasion.
- ★ Available in right hand and left hand.
- ★ Production according to TS EN 12385-4.


### Applications:

Used as tension rope. It can be used in the production of wire rope sling. Purse seine winch in construction is preferred. It can be used as elevator regulator rope. The machine can be used in suspended scaffold and facade cleaning system in case of motor suitability.



### GENERAL VIEW

Diameter Range (mm)	Rope Construction	Core	Number of Outer Strands	Number of Wires in Outer Strands	Rope Grades (N/mm <sup>2</sup> )	Metallic Area Factor
6 - 56	6x19 M	Fiber	6	114	1770, 1960	0.3570
6 - 56	6x19 M	Steel	6	114	1770, 1960	0.4180





## İZMİT 6x19 M STD

Rope Diameter (mm)	Minimum Breaking Load (kN)				Approximate Weight of 100 Mtrs. (kg)	
	1770 N/mm <sup>2</sup>		1960 N/mm <sup>2</sup>			
	Fiber Core	IWRC	Fiber Core	IWRC	Fiber Core	IWRC
3	4,89	5,77	5,42	6,39	3,11	3,43
4	8,69	10,30	9,63	11,40	5,54	6,10
5	13,60	16,00	15,00	17,70	8,65	9,53
6	19,60	23,10	21,70	25,50	12,50	13,70
7	26,60	31,40	29,50	34,80	17,00	18,70