


6xK26 WS-FC



6xK26 WS-IWRC

OLIVEIRA ZINCAL COMPACT

- ★ Excellent lifetime and performance
- ★ Excellent abrasion and wear resistance
- ★ Excellent resistance against crushing
- ★ Excellent fatigue resistance
- ★ Very high breaking load
- ★ Lower elongation of the wire rope
- ★ Better grease adherence


Applications:

Fishing wire rope for trawler.



GENERAL VIEW

| Diameter Range (mm) | Rope Construction | Steel Wire Rope Core | Number of Outer Strands | Number of Wires in Outer Strands | Rope Grade (N/mm ²) | Average Spin Factor |
|---------------------|-------------------|----------------------|-------------------------|----------------------------------|---------------------------------|---------------------|
| 19 - 36 | 6xK26 WS | FC | 6 | 156 | 1570 | - |
| 20 - 44 | 6xK26 WS | IWRC | 6 | 156 | 1570 | - |





OLIVEIRA ZINCAL COMPACT - FC

| Rope Diameter | Minimum Breaking Force 1570 N/mm ² | Weight |
|---------------|--|--------|
| (mm) | (ton) | (kg/m) |
| 19 | 23,00 | 1,46 |
| 20 | 25,32 | 1,61 |
| 22 | 30,33 | 1,93 |
| 24 | 36,14 | 2,29 |
| 25 | 39,79 | 2,52 |
| 26 | 42,40 | 2,69 |
| 28 | 50,28 | 3,18 |
| 30 | 56,95 | 3,62 |
| 32 | 64,82 | 4,12 |
| 34 | 73,12 | 4,64 |
| 36 | 82,06 | 5,21 |



OLIVEIRA ZINCAL COMPACT - IWRC

| Rope Diameter | Minimum Breaking Force 1570 N/mm ² | Weight |
|---------------|--|---------|
| (mm) | (ton) | (kg/m) |
| 20 | 28,75 | 28,720 |
| 22 | 34,56 | 34,550 |
| 24 | 41,28 | 41,330 |
| 25 | 45,06 | 45,070 |
| 26 | 48,22 | 48,220 |
| 28 | 56,88 | 56,940 |
| 30 | 64,53 | 64,540 |
| 32 | 73,70 | 73,710 |
| 34 | 83,38 | 83,400 |
| 36 | 93,07 | 93,110 |
| 38 | 103,47 | 103,460 |
| 40 | 115,29 | 115,360 |
| 42 | 126,71 | 126,700 |
| 44 | 139,35 | 139,440 |